

Single Phase String Inverter

SUN-7/7.5/8/9/10K-G



2 MPP trackers, Max. efficiency up to 97.7%



Zero export application, VSG application



String intelligent monitoring (optional)



Wide output voltage range



Anti-PID function (Optional)



Low start-up voltage of 80V

Deye

Stock Code: 605117.SH

Model	SUN-7K-G	SUN-7.5K-G	SUN-8K-G	SUN-9K-G	SUN-10K-G
PV String Input Data					
Max. PV Input Power (kW)	9.1	9.8	10.4	11.7	13
Max. PV Input Voltage (V)	550				
Start-up Voltage (V)	80				
MPPT Voltage Range (V)	70-500				
Rated PV Input Voltage (V)	360				
Max. Operating PV Input Current (A)	13+26			26+26	
Max. Input Short Circuit Current (A)	19.5+39			39+39	
No. of MPPT Trackers/ No. of Strings per MPPT Trackers	2/1+2			2/2+2	
AC Output Side					
Rated AC Output Active Power (kW)	7	7.5	8	9	10
Max. AC Output Apparent Power (kVA)	7.7	8.25	8.8	9.9	11
Rated AC Output Current (A)	31.8/30.4	34.1/32.6	36.4/34.8	40.9/39.1	45.5/43.5
Max. AC Output Current (A)	35/33.5	37.5/35.9	40/38.3	45/43	50/47.8
Rated Output Voltage/Range (V)	220/230 0.85Un-1.1Un				
Grid Connection Form	L/N/PE				
Rated Output Grid Frequency/Range(Hz)	50/45-55, 60/55-65				
Power Factor Adjustment Range	0.8 leading to 0.8 lagging				
Total Current Harmonic Distortion THDi	<3%				
DC Component of Grid	<0.5%In				
Efficiency					
Max. Efficiency	97.7%				
Euro Efficiency	97.2%				
MPPT Efficiency	>99%				
Equipment Protection					
DC Polarity Reverse Connection Protection	Yes				
AC Output Overcurrent Protection	Yes				
AC Output Overvoltage Protection	Yes				
AC Output Short Circuit Protection	Yes				
Thermal Protection	Yes				
DC Terminal Insulation Impedance Monitoring	Yes				
DC Component Monitoring	Yes				
Ground Fault Current Monitoring	Yes				
Power Network Monitoring	Yes				
Island Protection Monitoring	Yes				
Earth Fault Detection	Yes				
Overvoltage Load Drop Protection	Yes				
Residual Current (RCD) Detection	Yes				
Surge Protection Level	TYPE II(DC), TYPE II(AC)				
Interface					
Communication Interface	RS485/RS232 /WiFi/LAN				
General Data					
Operating Temperature Range (°C)	-25 to +65°C, >45°C Derating				
Permissible Ambient Humidity	0-100%				
Permissible Altitude (m)	2000m				
Noise (dB)	≤35 dB(A)				
Ingress Protection(IP) Rating	IP 65				
Inverter Topology	Non-Isolated				
Over Voltage Category	OVC II(DC), OVC III(AC)				
Cabinet Size (WxHxD mm)	330×410×198.5 (Excluding Connectors and Brackets)				
Weight (kg)	15.3				
Warranty	5 Years				
Type of Cooling	Natural Cooling				
Grid Regulation	IEC 61727, IEC 62116, EN 50549, NRS 097, RD 140, UNE 217002, G99				
Safety EMC/Standard	IEC/EN 61000-6-1/2/3/4, IEC/EN 62109-1, IEC/EN 62109-2				