

Hybrid Inverter

SUN- 8 K-SG05LP1-AU



Colorful touch LCD, IP65 protection degree



AC couple to retrofit existing solar system

16

Max. 16pcs parallel for on-grid and off-grid operation; Support multiple batteries parallel

190

Max. charging/discharging current of 190A

6

6 time periods for battery charging/discharging



Support storing energy from diesel generator

Deye

Stock Code: 605117.SH

Model		SUN-8K-SG05LP1-AU
Battery Input Data		
Battery Type	Lead-acid or Li-Ion	
Battery Voltage Range (V)	40-60	
Max. Charging Current (A)	190	
Max. Discharging Current (A)	190	
External Temperature Sensor	Yes	
Charging Curve	3 Stages / Equalization	
Charging Strategy for Li-Ion Battery	Self-adaption to BMS	
PV String Input Data		
Max. PV Input Power (W)	12000	
Rated PV Input Voltage (V)	370 (125-500)	
Start-up Voltage (V)	125	
MPPT Voltage Range (V)	150-425	
Full Load PV Voltage Range (V)	200-425	
PV Input Current (A)	26+26	
Max. PV I _{SC} (A)	39+39	
Number of MPPT / Strings per MPPT	2/2+2	
AC Output Data		
Rated AC Output and UPS Power (VA)	8000	
Max. AC Output Power (W)	8000	
AC Output Rated Current (A)	34.8	
Max. AC Output Current (A)	34.8	
Max. Continuous AC Passthrough (A)	50	
Peak Power (off grid)	2 time of rated power, 10 S	
Power Factor	0.8 leading to 0.8 lagging	
Output Frequency and Voltage	230V/240V0.85Un-1.1Un	
Grid Connection Form	L+N+PE	
Total Harmonics Current Distortion (THDi)	< 3% (of nominal power)	
DC current injection	<0.5% I _n	
Efficiency		
Max. Efficiency	97.60%	
Euro Efficiency	96.50%	
MPPT Efficiency	99.90%	
Protection		
Integrated	Anti-islanding Protection, PV String Input Reverse Polarity Protection, Insulation Resistor Detection, Residual Current Monitoring Unit, Output Over Current Protection, Output Shorted Protection, Surge protection	
Over Voltage Category	DC Type II/AC Type III	
Certifications and Standards		
Grid Regulation	AS/NZS 4777.2	
Safety EMC / Standard	IEC/EN 61000-6-1/2/3/4, IEC/EN 62109-1, IEC/EN 62109-2	
General Data		
Operating Temperature Range ()	-40 to +60 , >45 derating	
Cooling	Natural cooling	
Noise (dB)	<30 dB	
Communication with BMS	RS485; CAN	
Weight (kg)	24.9	
Size (mm)	330W x 580H x232D (Excluding connectors and brackets)	
Protection Degree	IP65	
Installation Style	Wall-mounted	
Warranty	10 Years	