

Three Phase String Inverter

SUN-18/20/25K-G05-AU



2 MPP trackers, Max. efficiency up to 98.6%



Zero export application, VSG application



String intelligent monitoring (optional)



Wide output voltage range



Anti-PID function (Optional)

Deye

Stock Code: 605117.SH

Model	SUN-18K-G05-AU	SUN-20K-G05-AU	SUN-25K-G05-AU
PV String Input Data			
Max. PV Input Power (kW)	27	30	37.5
Max. PV Input Voltage (V)	1100		
Start-up Voltage (V)	250		
MPPT Voltage Range (V)	200-850		
Rated PV Input Voltage (V)	600		
Max. Operating PV Input Current (A)	26+26		
Max. Input Short Circuit Current (A)	39+39		
No. of MPP Trackers/ No. of Strings MPP Tracker	2/2+2		
AC Output Data			
Rated AC Output Active Power(kW)	18	20	25
Max. AC Output Apparent Power(kVA)	18	20	25
Rated AC Output current (A)	26.1	29	36.2
Max. AC Output Current(A)	26.1	29	36.2
Rated Output voltage/range (V)	230V/400V 240V/415V 0.85Un-1.1Un		
Grid Connection Form	3L/N/PE		
Rated Output Grid Frequency/range(Hz)	50Hz/45Hz-55Hz		
Power Factor Adjustment Range	0.8 leading to 0.8 lagging		
Total Current Harmonic Distortion THDi	<3%		
DC Injection Current	<0.5In		
Efficiency			
Max. Efficiency	97.3%	98.5%	
Euro Efficiency	96.9%	98%	
MPPT Efficiency	>99%		
Equipment Protection			
DC Polarity Reverse Connection Protection	Yes		
AC Output Overcurrent Protection	Yes		
AC Output Overvoltage Protection	Yes		
AC Output Short Circuit Protection	Yes		
Thermal Protection	Yes		
DC Terminal Insulation Impedance Monitoring	Yes		
DC Component Monitoring	Yes		
Ground Fault Current Monitoring	Yes		
Arc Fault Circuit Interrupter (AFCI)	Optional		
Power Network Monitoring	Yes		
Island Protection Monitoring	Yes		
Earth Fault Detection	Yes		
Overvoltage Load Drop Protection	Yes		
Residual Current (RCD) Detection	Yes		
Surge Protection Level	TYPE II(DC), TYPE II(AC)		
Interface			
Communication Interface	RS485/RS232/CAN		
Monitor Mode	GPRS/WIFI/Bluetooth/4G/LAN(optional)		
General Data			
Operating Temperature Range (°C)	-25 to +65°C, >45°C Derating		
Permissible Ambient Humidity	0-100%		
Permissible Altitude (m)	4000m		
Noise (dB)	≤ 50 dB(A)		
Ingress Protection(IP) Rating	IP 65		
Inverter Topology	Transformerless		
Over Voltage Category	OVC II(DC), OVC III(AC)		
Cabinet Size (mm)	362W×527H×220D (Excluding Connectors and Brackets)		
Weight (kg)	20		
Warranty	10 Years		
Type of Cooling	Natural Cooling		
Grid Regulation	AS/NZS 4777.2		
Safety EMC/Standard	IEC/EN 61000-6-1/2/3/4, IEC/EN 62109-1, IEC/EN 62109-2		